aquamira.

PERFORMANCE DATA SHEET

67257 WaterBasics™ Emergency Pump and Filter Kit

General Use Information

The WaterBasics Pump and Filter Kit is designed to provide easy dispensing of stored emergency water and can be operated with or without the included filter. The system includes all the parts necessary to connect to most standard water containers. The retractable hose allows the user to fill containers up to 10 feet away from the storage container and conveniently stores on top of the container when not in use. A shutoff valve is included to prevent flow when not in use. The RED Line filter provides biological protection from cysts, bacteria and viruses. The system can be used with or without the RED Line filter but all health claims pertain only to the complete system with the RED Line filter correctly installed per the User Manual.

Important Safety Information

CAUTION - Do not connect pump directly to a pressurized water source, such as an inside or outside faucet. Incorrect use may result in damage or injury.

CAUTION - Pump and hose kit contain small parts. Keep away from Children.

General Maintenance

FILTER STORAGE - Filter may be stored wet for short periods of time. (<30 days) For long term storage (>30 days), Remove filter from Pump, remove excess water and allow to dry for a minimum of 48 hours. Store in a cool dry location. Do not store used filter in a sealed container. Do not freeze filter or expose filter to extreme temperatures.

PUMP, HOSE, AND FITTINGS STORAGE - Remove residual water, allow to air dry.

Replacement Parts

67259 WaterBasics Replacement Filter (RED-II-120)

Warranty and Disclaimer

Aquamira Technologies, Inc. (Aquamira) warrants all products to be free from defects in workmanship and materials for one year from the date of purchase by the consumer, or for the duration of the imprinted self life. Filter clogging or normal wear is not a defect. If you are not satisfied with the performance of an Aquamira product, Aquamira will repair or replace the product.

Aguamira hereby excludes any expressed or implied warranties of fitness for a particular purpose. The following is made in lieu of any such warranties: This information and specifications supplied by Aquamira are based on industry standards and are tested using standard laboratory test conditions which are accepted in the industry to be reliable, but Aquamira does not guarantee that any result shown or claimed will be obtained. Before using any Aquamira product, the user shall determine the suitability and the fitness of the products for their intended use. the effectiveness of Aquamira products may be limited by environmental or hygienic conditions, such as use with contaminated hands, recontamination after filtration or treatment, failure to maintain a sterile mouthpiece or downstream equipment, sharing with multiple users, exposure to extreme environmental conditions such as heat, freezing, severe shock such as drops or other impact that may damage the integrity of filters, seals or connections. The user assumes all risk and liability in connection with its own tests and use. Aquamira shall not be liable for any injury, loss or damage, direct or consequential, resulting by or from the use, misuse, or inability to use Aquamira products.

While testing was performed under standard laboratory conditions, acutal performance my vary.



Product Data and Dimensions

DIMENSIONS 12 x 4.5 x 4.5 inches

DRY WEIGHT 1.61 lbs (730 g)

FLOW RATE .05 - .21 gpm (200 - 500 ml/min)

 SERVICE LIFE (FILTER)
 120 gal (454.248 L)

 OP. TEMPS
 35 - 120°F (1.6 - 49°C)

 OP. PRESSURE (FILTER)
 3psi (20.6844kPa)

Recommended Use Conditions

Use best water source available, quality of the source water may vary, use only Aquamira RED Line Series II filters if biological quality of source water is uncertain.

Assembled in US of US & Global Components. Filter made in the USA. EPA Est. No 71766-UT-001

Certifications



Certified by IAPMO R&T to US EPA Microbiological Purifier test standard for the reduction of cysts, bacteria and viruses. Certified to NSF/ANSI 372 for lead free content.

Performance Specifications

