

# MILE MARKER

# TRAILER/UTILITY

## SEC4500



### VERSATILE DESIGN AND LOW AMPERAGE DRAW

The SEC4500 is a versatile, utility recovery tool that serves large side by side units just as well as trailer duty. This winch revolutionizes efficiency and performance with its compact size, low amperage draw, and fast line speeds. The Mile Marker SEC4500 winch includes a mounting plate, as well as an 8' tow strap for protecting valuable cargo from cable damage.

### FEATURES:

- 3.7 HP Series Wound Motor
- Rugged Planetary Gear Sets
- Clockable Gear Housing
- Fast Line Speeds
- Submersible, 250 Amp Solenoid
- Automatic Load Holding Brake
- Corrosion Resistant Stainless Steel Fasteners
- 79' Steel Cable
- Roller Fairlead
- Waterproof
- Handheld Remote Control
- Includes Tow Strap
- Includes Mounting Plate

### SPECIFICATIONS:

Part Number	76-50115BW
Rated Line Pull	4500 lbs (2043 kg)
Gear Train	3 Stage planetary
Gear Ratio	150:1
Motor	12 V DC, input power: 3.7Hp (2.7kw) 24 Volt available
Remote	Power in, Power out with 12' cable (3.7 m)
Dimensions (LxWxH)	17.3" X 6.3" X 7.8" (440 mm X 161 mm X 200 mm)
Steel Cable	1/4" X 79' (6.3 mm X 24 m) (7,000 lb. breaking strength)
Drum Size Diameter/Length	2.5" X 5.5" (63 mm X 140 mm)
Net weight	49 lbs (23 kg) (with mounting plate)
Bolt Pattern	4 bolt pattern 6.5" X 4.5" (165.9 mm X 114.3 mm)

### PERFORMANCE:

Line Pull		Line Speed		Motor Current
lb	kg	fpm	mpm	amps @ 12 V
0	0	14	4.3	35
1500	681	6.6	2	80
3000	1362	4.6	1.4	145
4500	2043	3.3	1	170

Layer	Rated Line Pull		Cable Capacity	
	lb	kg	ft	meters
1	4500	2043	15	4.6
2	4264	1935	31.5	9.6
3	3725	1691	50	15.2
4	3307	1501	70	21.3



MOUNTING PLATE INCLUDED



TOW STRAP INCLUDED